

DATA SHEET

1" Phantom XD™ EN

The Phantom XD selectable flow nozzle series has your target flow covered! With low pressure options available there is one to meet your needs. Built with positive interlocking robust tactile selection grips, choosing the desired flow rate will not be a problem even in the harshest conditions. Its durability and efficiency are unmatched by any other selectable flow nozzle on the market.



Specifications:

Phantom XD EN Tip	Combination selectable/fog
	50-100-150-250 lpm @ 6 & 7 BAR
	100-250-350-500 lpm @ 6 or 7 BAR
	Fog Teeth – standard spinning stainless steel or fixed molded urethane
	Quarter turn adjustable fog @ >100° attack pattern
	50–250 lpm - flush feature allowing 3.2mm debris to pass through
	100–500 lpm - flush feature allowing 4.8mm debris to pass through
	Raised lug on tip and grip selector to indicate to stream pattern and flow
XD Shutoff	Teflon coated forged aluminum body
	1" (25 mm) free swivel inlet (BSP, NHT, NPSH, BSPP or custom threads)
	1" (25 mm) waterway
	Hard coated forged aluminum bale handle
	Hard coated aluminum ball valve gives minimum frictional loss.
	Optional ergonomic Pistol Grip
Weight	Laser etched indicators with customizable logo option
	50–250 lpm - 1.7kg w/ Pistol Grip, 1.4kg w/o 100–500 lpm - 2.2kg w/ Pistol Grip, 1.9kg w/o
Overall Dimensions	50–250 lpm - 269 mm x 258 mm x 109 mm 100–500 lpm - 297 mm x 258 mm x 109 mm
	50–250 lpm - BS EN 15182-4, PN40 100–500 lpm - BS EN 15182-2, PN16
Certification	
Bumper/Grip Insert	UV Resistant Thermo Plastic Vulcanizate (TPV)
	Standard red

Color Options:

