



WYES

APPLIANCES

## Wyes

Used to divide a single flow, usually at a fireground scene, wyes must be both reliable and intuitive to use. Elkhart offers several customizable handle options. All Elkhart wyes give years of dependable service. When necessary, they are easy to field service and re-buildable for continued long-term use.



4-7

INLET SIZE (FEMALE)	OUTLET SIZE (MALE)					TYPE		HANDLE STYLE					MATERIAL/TRIM		DIMENSIONS		MODEL	FIGURE
	0.75"	1"	1.5"	2.5"		Plain	Ball Valved	Knob	Short Elk-O-Lite®	Long Elk-O-Lite®	Molded Urethane	Positive Twist Lock	Brass / Chrome	Elk-O-Lite® / Hard Anodized	Length (Inches)	Weight (Lbs.)		
	(x2)	(x2)	(x2)	(x2)	(x3)													
1.0" NHT		•				•		o	s	o			•	5.5	1.8	B-100-SA	2	
1.5" NHT	•	•				•		o		s			•	5.5	1.8	B-100-SA	2	
			•			•		o		s			•	5.5	8.5	B-100-L	2	
			•			•		o		s			•	5.5	3.9	B-100-LA	2	
2.5" NHT			•			•		o	o	s	o		•	5.5	4.5	B-100-A*	2	
			•			•		o		s			•	5.5	9.0	B-100	2	
			•			•				s			•	4.8	1.2	1A	3	
			•			•				s			•	9.0	14.5	B-97A	1	
			•			•				s			•	9.0	31.0	B-97	1	
			•			•							•	7.6	2.6	1A	3	
3.5" NHT			•			•					s		•	9.0	14.5	B-97A	1	
			•			•					s		•	9.0	31.0	B-97	1	
4.0" NHT			•			•					s		•	9.0	14.5	B-97A	1	
			•			•					s		•	9.0	31.0	B-97	1	
4 <sup>3</sup> / <sub>4</sub> " STORZ			•			•					s		•	10.5	16.0	B-97A	1	
4.5" NHT			•			•							•	7.9	4.8	1A	3	
			•			•							•	8.8	15.8	1	3	
			•			•					s		•	9.0	14.5	B-97A	1	
			•			•					s		•	9.0	31.0	B-97	1	
5 <sup>1</sup> / <sub>2</sub> " STORZ			•		•						s		•	10.5	16.0	B-97A	1	
5.0" NHT			•			•					s		•	9.0	14.5	B-97A	1	
			•			•					s		•	9.0	31.0	B-97	1	
6.0" NHT			•			•					s		•	9.0	14.5	B-97A	1	
			•			•					s		•	9.0	31.0	B-97	1	

KEY s = standard o = option  
 \* Optional pressure gauge available



## WYES

**FIGURE 1**

**B97/B97A (2-WAY) – POSITIVE TWIST LOCK**



*Fig. 1*

**FIGURE 2**

**B-100/B-100A**



*Fig. 2*

**FIGURE 3**

**1/1A**



*Fig. 3*

Figures depict general product types only and are not intended to be inclusive of all product features.

## OPTIONS

HANDLES					PRESSURE GAUGE	THREADS
						<i>All fireground connections are NHT unless otherwise specified. See index T-13 for optional base threads.</i>
Knob	SHORT (ELK-O-LITE®)	LONG (ELK-O-LITE®)	MOLDED URETHANE	POSITIVE TWIST LOCK		
<ul style="list-style-type: none"> <li>• Not all handles available on all models.</li> <li>• All twist-locks feature metal knurled knobs.</li> </ul>						

## PSI RATING

While all Elkhart wyes are rated to at least 200 psi (13.79 bar), the products specified below are rated to 300 psi (20.69 bar):

- B-100-A (2.5" F inlet)
- B-100-LA (1.5" F inlet)
- B-100-SA (1.0" F or 1.5" F inlet)