

























# MASTER STREAM
























## SELECTOR GUIDE

# MASTER STREAM

6-1

	AVAILABLE BASE	PRODUCT	DESCRIPTION	MATERIAL			"QUICK-KEY"
				Brass	Composite	Elk-O-Lite®	
<b>FIXED</b>	<b>5000E</b> Available GPM (LPM) 15-475 (57-1798)	 Page 6-3	<ul style="list-style-type: none"> <li>Combination nozzle</li> <li>12 or 24 VDC enclosed and sealed motor</li> </ul>	Brass Composite Elk-O-Lite®	 		
						1.5 2.5 3.5	
<b>AUTOMATIC</b>	<b>SIM-10FE</b> Available GPM (LPM) 20-120 (76-454)	 Page 6-3	<ul style="list-style-type: none"> <li>Simplifies fireground hydraulics</li> <li>Maintains effective flow stream</li> <li>12 or 24 VDC enclosed and sealed motor</li> </ul>	Brass Composite Elk-O-Lite®	 		
						1.5 2.5 3.5	
<b>FIXED/SELECTABLE</b>	<b>R.A.N.</b> Available GPM (LPM) 250-500 (946-1893)	 Page 6-5	<ul style="list-style-type: none"> <li>Designed for use with R.A.M.</li> <li>Integral stream shaper</li> <li>1/4 turn stream adjustment</li> <li>Optional oscillating configuration available</li> </ul>	Brass Composite Elk-O-Lite®	  		
						1.5 2.5 3.5	
<b>AUTOMATIC</b>	<b>X-STREAM®</b> Available GPM (LPM) 300-2000 (1136-7571)	 Page 6-6	<ul style="list-style-type: none"> <li>Simplifies fireground hydraulics</li> <li>Maintains effective flow stream</li> <li>Calibrated at lower pressures - 75 &amp; 80 PSI</li> </ul>	Brass Composite Elk-O-Lite®	      		
						1.5 2.5 3.5	
<b>SELECTABLE</b>	<b>6000</b> Available GPM (LPM) 15-700 (60-2700)	 Page 6-9	<ul style="list-style-type: none"> <li>Designed for use with Sidewinder EXM</li> <li>Maintains effective flow stream</li> <li>Motor enclosed and sealed</li> </ul>	Brass Composite Elk-O-Lite®	 		
						1.5 2.5 3.5	
<b>FOAM EXPANSION TUBES</b>	Available GPM (LPM)	 Page 6-10	<ul style="list-style-type: none"> <li>Quick-snap connection</li> <li>Composite or metal construction</li> </ul>	Brass Composite Elk-O-Lite®	 		
						1.5 2.5 3.5	

	AVAILABLE BASE			PRODUCT	DESCRIPTION	MATERIAL			"QUICK-KEY"	
	1.5	2.5	3.5			Brass	Composite	Elk-O-Lite®		
<b>FIXED</b>	<b>SELECT-O-STREAM®</b>			 <i>Page 6-11</i>	<ul style="list-style-type: none"> <li>Fully machined waterway for excellent stream quality</li> <li>Large handles for easy stream pattern management</li> <li>Constant Flow Nozzle</li> </ul>	•	•	•	  	
	Available GPM (LPM) 350-1000 (1325-3785)									
<b>SELECTABLE</b>	<b>SELECT-O-FLOW®</b>			 <i>Page 6-13</i>	<ul style="list-style-type: none"> <li>Large handles for easy stream pattern management</li> <li>Operator set flow and stream</li> <li>Selectable Flow Nozzle</li> </ul>	•	•	•	  	
	Available GPM (LPM) 300-1250 (1136-4732)									
<b>FIXED</b>	<b>MYSTERY</b>			 <i>Page 6-14</i>	<ul style="list-style-type: none"> <li>Created for Industrial applications</li> <li>Large handles for easy stream pattern management</li> <li>Low maintenance</li> </ul>	•	•	•	  	
	Available GPM (LPM) 350-2000 (1325-7571)									
<b>AUTOMATIC/FIXED</b>	<b>SELF-EDUCTING</b>			 <i>Page 6-15</i>	<ul style="list-style-type: none"> <li>Self-educating Class A and B foam</li> <li>1/2%, 1%, 3%, or 6% proportioning</li> <li>Field-adjustable foam proportioning</li> </ul>	•	•	•	    	
	Available GPM (LPM) 350-2000 (1325-7571)									
<b>ADJUSTABLE/FIXED</b>	<b>FIXED SYSTEM</b>			 <i>Page 6-19</i>	<ul style="list-style-type: none"> <li>Designed for use in fixed system applications</li> <li>Field-adjustable flow rate and fog pattern up to 120°</li> </ul>	•	•	•	 	
	Available GPM (LPM) 5-1000 (20-3780)									

**KEY:**

											
Electrical Operation	Manual Operation	Remote Control Operation	Hydraulic Operation	Hazardous Location	Self-Educting Foam	Foam Compatible	Underwriters Laboratories	Twist Shut-off Available	Low Pressure Available	Conformity European	Factory Mutual